

GRAPHICS - RI-MARK

Issue date : 13/01/2011
Date last modification : 10/10/2012**06899 - RI-MARK APPLICATION FILM CF300 CLEAR FILM****Face Material**

Clear embossed polypropylene application tape with excellent flatness. It is dimensionally stable, easy to unwind, position and will not stretch or curl.

Type	Polypropylene	
Colour and Finish	Clear embossed	
Weight	82 g/m ² ±10%	ISO-536
Thickness	90 µ ±10%	ISO 534-80

Adhesive

The adhesive is plasticizer resistant and ensures a strong initial tack to all types of vinyl films. The application tape is easily removed without leaving any residue, even if left in place for a period of time.

Type	Permanent acrylic
Tack	1.5 N/inch ²

Liner

Type	n/a
Colour and Finish	n/a

Applications

Suitable for transferring self-adhesive signs and lettering produced from cast or calendered plotter films with a matt or gloss finish.

Printing Methods

Suitable for wet application.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

